

3-Line Business IP Phone for Maximal Office Productivity

- 132 x 64 graphic LCD, TI Titan chipset
- HD Voice: HD Codec, HD speaker, HD handset
- 3 Programmable keys, 4 Text-Sensitive soft keys
- PoE & mains power (SIP-T22P) or PoE only (SIP-T22PEX)



Yealink SIP-T22P features an intuitive user interface and enhanced functionality which make it easy for people to interact and maximize productivity. With TI 's leading VoIP voice engine, it enables enhanced high-fidelity audio,outsourced management options, flexible deployment and third-party communications applications. As a cost effective IP solution, it helps users to streamline business processes, delivering a powerful and consistent communications experience for small and large offices environment.

Network Features

SIP v1(RFC2543), v2(RFC3261)
 3 User accounts
 NAT Transverse: STUN mode
 IP Assignment: Static/DHCP/PPPoE
 In-Band DTMF, Out-of-Band DTMF, SIP Info
 Proxy mode and Peer-to-peer SIP link mode
 TFTP/DHCP/PPPoE client
 Telnet/HTTP server
 DNS client
 NAT/DHCP server
 Support VLAN, QoS
 PoE optional

Voice Features

Wideband Codec: G.722, voice spectrum between 50-7000Hz
 Narrowband Codecs: G.711, G.726, G.723.1/iLBC, G.729AB and GSM
 VAD, CNG, AEC, PLC, AJB, AGC
 Full-duplex hands-free speakerphone

Telephony Features

Call Hold, Call Waiting, Call Transfer, Call Forward
 Caller ID, Call List, DND, Redial, Flash
 3-way Conference, Speed Dial
 Personal Ring Tone, Voicemail
 Volume Adjustment, Mute, Speakerphone

IP PBX System Integration

Dial Plan, Dial-now, Paging
 Remote/Local XML Phonebook
 Call Park, Call Pickup, Distinctive Ringtone
 Auto-answer, intercom

Config, Upgrade and Usage

Language Customization Support
 Firmware Upgrade: TFTP/Console/Auto-provision
 Auto-provision: TR069 Optional
 Direct IP call without SIP proxy
 Dial number via SIP server
 Dial URL via SIP server

Security

Secure RTP
 Digest authentication using MD5/MD5-sess
 Secure configuration file via AES encryption

Physical Features

TI Titan Chipset
 LCD: 132x64 with blue backlit
 3 programmable keys, 4 text-sensitive keys
 23 hard keys, 2 indication LEDs
 Headset port: RJ-9
 Network Interface: 2x RJ45 10/100M ports
 Dimension: 185 X 200 X 90mm
 SIP-T22P: PoE & mains; SIP-T22PEX PoE only
 Power adapter: Input: AC 100~240V
 Output: DC 5V/1.2A
 Operating humidity: 10~95%
 Storage temperature: up to 60°C

Package Features

Qty/CTN: 10 PCS
 N.W/CTN: 22.86KG
 G.W/CTN: 25.26KG
 Measurement: 0.073CMB
 Carton Meas: 565 x 550 x 235MM

Certifications

