

# snom 300

SIP based VoIP Phone

snom OCS  
edition

a premier  
snom phone

CTI  
inside



- **Two-line display (2x16 characters)**
- **27 keys, 7 LEDs**
- **6 programmable function keys**
- **2x IEEE 802.3 10/100 Mbps switch**
- **4 SIP identities (lines)**
- **Headset connection**
- **SIP RFC3261**
- **Security: SIPS/SRTP, TLS**
- **STUN, ENUM, NAT, ICE**
- **Codecs: G.711, G.729A, G.723.1, G.722, G.726, GSM 6.10 (full rate)**
- **Power over Ethernet (PoE)**
- **XML driven mini-Browser**
- **Very low energy consumption**

The IP telephone with the latest VoIP technology for the discerning caller! Ideal for ITSPs, offices, and private users.

As the basic model of the snom business telephone family, the SIP telephone **snom 300** fulfils the requirements of VoIP telephony and additionally offers numerous functions that are indispensable for everyday working life. Due to its excellent cost-performance ratio, it is ideal both for ITSP packages/products and for small and medium-sized enterprises, home offices, and private users.

The **snom 300** sets new standards when it comes to user-friendliness: A two-line LCD display shows call infor-

mation, and the menu-driven user interface provides simple feature management.

The **snom 300** is synonymous with effectiveness, time saving and flexibility: It provides all necessary office functionalities, for example choice of outgoing identity, "busy" indication, or picking up calls. Four different identities are possible.

Six user- or administrator-configurable (or carrier-preconfigurable) function keys can easily be allocated to arbitrary menu functions like DND, redirection, deny, etc., or assigned to multiple lines. The **snom 300** comes factory-equipped with two of its six

programmable keys configured as line appearances. You can configure up to all six function keys this way – flexible enough to suit the needs of every user.

Are you afraid of unsolicited eavesdroppers, data theft, or spam calls? Thanks to the **snom 300** you have no need to worry. Due to the security standards SRTP and SIPS, the **snom 300** is just as secure as the business models snom 360 and 320. This makes it perfectly suited for use in sensitive environments such as in banks and medical or military establishments.

# Technical Data snom 300

## GENERAL FEATURES

- **Dimensions:**  
approx. 20x18.5x12 cm
- **Weight:** approx. 730 g
- **Safety:** IEC 60950-1:2001,  
CB Test Certificate: DE 02011039
- **Certifications:** FCC Class B, CE Mark
- **Power consumption:** 1.7–2.7 watts
- **Colors:** available in snomBLACK and  
snowWHITE

## CONNECTORS

- **1 x LAN, 1 x PC:** RJ45 (Ethernet)
- **Power:** 5 V DC
- **Ethernet:** 2x IEEE 802.3 10/100 Mbps switch
- **Power over Ethernet:** IEEE 802.3af,  
Class 1
- **Handset:** RJ11 connector
- **Headset:** RJ11 connector

## USER INTERFACE

- 2x16 character display, backlit
- 27 keys, 6 programmable function keys  
with LEDs
- Caller-ID
- Message waiting indication LED
- Address book (100 entries)
- Speed dialing
- Local dial plan
- Number guessing
- Lists of missed, received and dialed calls  
(100 entries each)
- Call waiting indication
- Clock, daylight saving, call-timer
- Call blocking (deny list)
- Blocking of anonymous calls
- Handling of 4 simultaneous calls
- Menu-driven user interface

- Ring tone selection, import of individual  
ring tones
- URL Dialing support
- National language support for selected  
languages (NLS)
- Do not disturb
- Speakerphone (full duplex)
- Auto answer mode
- Keyboard lock

## CALL FEATURES

- Hold
- Blind transfer, attended transfer
- Music on hold support (only via PBX)
- Divert
- Conferencing (3-way conference bridge  
on phone)
- Call park, call pick-up (only via PBX)
- Call completion
- Client Matter Code (CMC)
- Call waiting/switching between calls
- Redialing
- RTP multicast paging
- Multiple audio device support

## WEB SERVER

- Embedded web server HTTP/HTTPS
- Easy configuration of the phone, remote  
configuration
- Dial from web interface
- Password protection
- Diagnostics (tracing, logging, syslog)

## SECURITY, QUALITY OF SERVICE

- HTTPS (server/client)
- Transport Layer Security (TLS)
- SRTP (RFC3711), SIPS
- RTCP, S-RTCP
- VLAN (802.1 pq)

## CODECS, AUDIO

- G.711 A-law,  $\mu$ -law
- G.729A, G.723.1, G.727
- GSM 6.10 (full rate)
- G.722
- Comfort noise, voice activity detection

## SIP

- RFC3261 compliance
- UDP, TCP and TLS
- Digest/basic authentication
- PRACK (RFC3262)
- Error-information support
- Reliability of provisional responses  
(RFC3262)
- Early media support
- DNS SRV (RFC3263),  
redundant server support
- Offer/answer (RFC3264)
- Message Waiting Indication (RFC3842),  
subscription for MWI events (RFC3265)
- Dialog-state monitoring (RFC 4235)
- In-band DTMF/out-of-band DTMF/  
SIP INFO DTMF
- STUN client, ICE (NAT traversal)
- ENUM (RFC3261), NAPTR (RFC2915),  
rport (RFC3581), REFER (RFC3515)
- Bridged line appearance (BLA)
- Auto provisioning with PnP
- Busy lamp field support (BLF)

## INSTALLATION

- Automatic software update
- Automatic settings retrieval  
via HTTP/HTTPS/TFTP with authentication
- Installation via web interface
- Static IP provisioning, DHCP
- NTP



**1800 817 807**  
sales@alloy.com.au  
www.alloy.com.au

Proudly distributed in Australia by

**Alloy Computer Products Australia Pty Ltd**

### Melbourne

4/585 Blackburn Road  
Notting Hill, VIC 3168  
Tel: (03) 8562 9000  
Fax: (03) 9561 7412

### Canberra

2/42 Geils Court  
Deakin, ACT 2600  
Tel: (02) 6291 4922  
Fax: (02) 6291 8100

### Sydney

99 Baxter Road  
Mascot, NSW 2020  
Tel: (02) 8080 9600  
Fax: (02) 8080 9602